



GENERAL NOTES:
 1 - ENCLOSURE - 3mm ALUMINIUM
 2 - ENCLOSURE FINISH - POWDER COATED RAINFOREST GREEN G15
 3 - TRANSFORMER PAINT STORM GREY N42
 4 - IP RATING
 TRANSFORMER COMPARTMENT - IP23D
 HV COMPARTMENT - IP44
 LV COMPARTMENT - IP44
 5 - REFER TO 66403514 FOR HV PROTECTION WIRING DIAGRAM.
 6 - COMPONENTS HIDDEN IN CERTAIN VIEWS FOR CLARITY

QTY.	ITEM	DESCRIPTION
1	14	LV BOARD
1	13	RM6 IDI
1	12	AU-9-DL GNSS & LTE MIMO COMBO ANTENNA
2	11	SWITCH DOOR P/BUTTON 250V .25A
2	10	SIGN DANGER-HIGH VOLT KEEP OUT
1	9	MAIN EARTH BAR
1	8	RM6 EXTENDED HANDLE 700MM POSITION
1	7	PRESSURE RELIEF DEVICE
1	6	NAME PLATE 1500KVA 11/0.433KV DYN1 +5 TO -7.5 IN 2.5% STEPS
1	5	T/C, ROTARY 33KV,6POS,100A,COMEM
1	4	MASS PLATE KK 1500KVA
2	3	LIGHT 4W LED DOUBLE INSULATED
1	2	OIL PRESENCE INDICATOR
1	1	KIOSK ID PLATE

Scale: 0.027	Technical Specification: ISO 2768cL, ISO 8015	Units of measure: mm, gr, cm2, cm3
--------------	---	------------------------------------

		Document Description: AUSGRID KK 1500KVA 11/0.433 DYN1 KIOSK ASSEMBLY	Doc. Rev. 03	Sheet: 1/1
		Document Number: SCHNEIDER_GA_KK	State:	

03	19/12/23
02	22/11/23
01	03/07/23
00	28/09/21
REV	DATE

AUSGRID 269244-1

SUMMARY OF MASS:-		
KIOSK TOTAL	5950	kg

The Schneider Electric brand and any trademarks of Schneider Electric SE and its subsidiaries referred to in this drawing are the property of Schneider Electric SE or its subsidiaries. All other brands may be trademarks of their respective owners. This drawing and its content are protected under applicable copyright laws and furnished for informational use only.